

BEST AVAILABLE COPY

GOIR 33/28

H01F7/02

(54) MAGNETIC FIELD GENERATING DEVICE

(11) 61-114148 (A) (43) 31.5.1986 (19) JP


(21) Appl. No. 59-236970 (22) 9.11.1984

(71) SUMITOMO SPECIAL METALS CO LTD (72) SEIJI ENDO(1)

(51) Int. Cl. G01N24/06, A61B10/00, H01F7/02

PURPOSE: To obtain a tomographic image of a necessary object of diagnosis through a relatively small-sized gap by detecting relative positions of a target in the three-axial coordinate system of the object of diagnosis and the three-axial coordinate system of a moving means in a magnetostatic field, and making a uniform magnetic field coincident.

CONSTITUTION: A magnetic circuit 1 has a couple of plate type magnetic pole pieces 3 whose main surface face each other at a constant interval, columnar permanent magnets 2 are connected between both end facing parts of the magnetic pole pieces 3 to form the gap 4 between the magnetic pole pieces 4, and pieces of magnetic flux produced by the magnets 2 are equalized in direction and form magnetic fields through the magnetic pole pieces 3, thereby forming a uniform magnetostatic field part 5 which is intense within a sphere having a radius (r) and has extremely high uniformity in the gap 4 as center. The whole of the circuit 1 is moved by a linear motor 6 in three axial directions. The object of diagnosis mounted on a rack which is movable in the three axial directions is sent in the three-axial coordinate system of this moving device and the magnetostatic field part 6 is moved to the necessary target; and the position of the magnetostatic field part 5 is measured 7 by arithmetic on the basis of input electric power to the motor 6, which is controlled 8 according to the measurement result to make the object coincident with target coordinates.



8: controller

DOC

Non-file